

DKX Series Type III

High Security Pedestrian Door Lock



- FF-L-2890C Type III GSA Approved
- CDX-10, Dorma F9300, 3-hour rated exit device and dormakaba P2000 stand-alone access control - Type III
- Simultaneous retraction of the CDX-10 deadbolt and deadlatch

Kaba Mas high security combination locks are used for GSA approved security containers. The DKX series pedestrian door locks are used on doors to secure rooms as well as Secure Compartmented Information Facilities (SCIFs). Kaba Mas products have been trusted and preferred selections by U.S. Government agencies and Government contractors since our X-O series was introduced in 1992.

DKX Series Type III

The Kaba Mas DKX Series was developed to meet changes to Federal Specification FF-L-2890C. These changes included a life-safety requirement to locking devices used to protect any secure areas occupied by Government and/or cleared contractor personnel.

The Type III is comprised of a CDX-10, which is utilized with the Dorma F9300 3 hour fire rated exit device and a dormakaba PowerPlex P2000 Grade 1, heavy duty cylindrical lock for use on outswing doors only.

Together, it ensures simultaneous retraction of both the secondary cylindrical lock dead latch and the CDX-10 primary dead bolt. The combination of products ensures compliance with codes for security, fire, and life safety as well as adheres to requirements of the American with Disabilities Act (ADA).

Specifications/Standards/Regulations

Life Safety

Meets/Compliant with:

- ANSI/BHMA A156.2, Series 4000, Grade 1
- UFAS, ADA, IBC, NFPA Code 80/101 compliant
- ANSI/BHMA A117.1

Security

The Kaba Mas X-10 High Security Combination Lock used with the DKX Series product line will meet or exceed performance requirements set by Federal Specification FF-L-2740C for protection of Classified and National Security Information (NSI).

Key Features and benefits:

- Combines proven, time-tested, products - Kaba Mas CDX-10, Dorma F9300 3-hour fire rated exit device and PowerPlex P2000
- Offers multi-user capability (100 users),
- Capable of 1000 audits events
- Features request to exit
- Weather resistant for outdoor use (P2000)
- Vandal resistant solid metal pushbuttons
- Programming via keypad or software (optional)
- 4 to 8 digit PIN code
- All available with black dial and dial ring mounting plate
- The CDX-10 features a convenient back-lit LCD viewer to assist in low light usage conditions
- The DKX Series is designed to accept all GSA approved FF-L-2740B combination locks
- P2000 available with small format interchangeable core (SFIC) or standard KIL configurations
- Training and certification are available upon request

For more information contact Kaba Mas

Kaba Mas LLC
1051 Newtown Pike, Ste. 150
Lexington KY 40511
T: 859 479 1329

kabamas.com

KM.X.O.DKXL-FS.04_24_20